

+33 (0)3 89 78 32 51 T

133 (0)3 03 10 32 31 1

+33 (0)3 89 47 18 56 F

www.corplex.com

Declaration of Performances/Regulation EU 305/2011 Annex III

Dop No. 2007000-1

1) Unique identification code of the product-type

Light transmitting flat multiwall polycarbonate sheet AKYVER® SUN TYPE 20-7W 3400 CLEAR

2) <u>Intended use or uses of construction product, in accordance with the applicable harmonized technical specification</u>

For roofing and cladding of buildings and/or 'internal and external use for walls and ceilings

3) <u>Manufacturer</u>

Corplex France Kaysersberg 75 Route de Lapoutroie 68240 Kaysersberg, France T +33 (0)3 89 78 32 51 F +33 (0)3 89 78 38 56 www.corplex.com

4) Authorised representative

Non applicable

5) System or systems of assessment and verification of constancy of performances of the construction product System 3

6) In case of the declaration of performance concerning a construction product covered by a harmonized standard Non applicable

7) Declared performances

 ϵ

68240

| External fire performance | F_{roof} | |
|--|----------------------------------|----------------|
| Reaction to fire | B s1 d0 | |
| Resistance to fire | NPD | |
| Water vapour permeability | 3,8 x 10 ⁻⁵ mg/m h Pa | |
| Water/ air permeability | Pass | |
| Release of dangerous substances | NPD | |
| Dimensional tolerances | Pass | |
| Shatter properties (save breakability) as: | | |
| - Small hard body impact resistance | Pass | |
| -Large soft body impact resistance | NPD | |
| Mechanical resistance | Bx= 317,7 Nm ² /m | |
| (deformation behaviour) | By= 100.1 Nm ² /m | |
| | Sy= 2401 N/m | EN 16153: 2015 |
| | Mb= 68.4 Nm/m | |
| Direct airborne sound insulation | NPD | |
| Thermal transmittance | NPD | |
| Light transmittance | NPD | |
| Total solar energy transmittance | NPD | |
| Resistance to fixings | Fixing method (see the | |
| | manufacturer's informations) | |
| Durability, as variation (after ageing) | | |
| - Of yellowness index | ΔΑ | |
| - Of light transmittance | ΔΑ | |
| - Of deformation flexural modulus | Cu 0 | |
| - Of tensile strength | Ku 0 | |

8) The performances of the product identified in point 1 are in conformity with the declared performances in point 7. This declaration of performances is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

Name: GOEPFERT Felix Function: Technical manager AKYVER®

Place and date of issue: Kaysersberg, 07th September 2020 Signature:

9